

GENERAL SPECIFICATIONS
ATTACHMENT "A"
RFQ 403617
MOHAWK FLOORING MATERIAL (NO SUBSTITUTIONS)

1. CARPET TILE – 5,500 SQ. YD.

Manufacturer:	Mohawk Group
Description / Style:	BT400 New Basics III Tile
Product Type:	Carpet Tile
Color:	978 Mineralite
Construction:	Tufted
Surface Texture:	Textured Heather Loop
Gauge:	1/10" (39.37 rows per 10 cm)
Density:	5,684
Weight Density:	102,315
Stitch per Inch:	7.4 (29.13 per 10 cm)
Finished Pile Thickness:	114." (2.90 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex Matrix
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	18.0 oz per sq. yd. (610 g/m2)
Size:	24" x 24" (.6096 m x .6096 m)
Soil Release Technology:	Sentry Soil Protection
Installation Method:	Brick Ashlar, Vertical Ashlar, Quarter Turn
Indoor Air Quality:	CRI Green Label Plus GLP 1171
Foot Traffic Recommendation TARR:	Heavy
NSF 140:	EcoFlex NXT - NSF 140 Gold

2. ADHESIVE – 4 GALLON UNITS

Enpress Adhesive	Up to 95% in-situ RH and a PH of 12.0
------------------	---------------------------------------